



Choose the product according to required features and purpose of use.
Call +39 (06) 931-5492 (International) or +1 (773) 645-8113 (US only) for more info

Comparison Matrix



| | T150 LC | | T150 | | T170 | | | | Oversize | | |
|------------------------------|-------------------|-----------------------|---------|---------|---------|--------------------------|----------------|-------------------|----------|---------|---------|
| | E LC DE LC | E LC MED DE LC MED | DE | DE MED | DE | D MED E MED DE MED | DE Sportmed | DE 3p Sportmed | T200 S | T200 M | T250 MR |
| Dimensions | | | | | | | | | | | |
| Running surface length (cm) | 150 | 150 | 150 | 150 | 170 | 170 | 170 | 170 | 200 | 200 | 250 |
| Width (cm) | 50 | 50 | 50 | 50 | 65 | 65 | 65 | 65 | 75 | 100 | 100 |
| Weight (Kg) | 210 | 210 | 210 | 210 | 321 | 340 | 341 | 380 | 850 | 1000 | 1100 |
| Performance | | | | | | | | | | | |
| Speed (km/h) | 0.0-18 | 0.0-18 | 0.0-22 | 0.0-22 | 0.0-30 | 0.0-30 | 0.0-40 | 0.0-40 | 0.0-40 | 0.0-40 | 0.0-40 |
| Elevation Range | 0-20% | 0-20% | 0-25% | 0-25% | 0-28% | 0-28% (E & DE only) | ±28% | ±25% | ±35% | ±35% | ±27% |
| Maximum Patient Weight (kg) | 250 | 250 | 300 | 300 | 200 | 200 | 200 | 200 | 300 | 300 | 300 |
| Special Speed (km/h) | 0.0-22 | 0.0-22 | | | 0.0-45 | 0.0-45 | 0.0-45 | 0.0-45 | 0.0-80 | 0.0-80 | 0.0-80 |
| Special Applications | | | | | | | | | | | |
| Reverse belt rotation | ○ | ○ | ○ | ○ | ○ | ○ | ● | ● | ● | ● | ● |
| Pull cord (emergency off) | ● | ● | ● | ● | ● | ● | ● | ● | ○ | ○ | ○ |
| Safety arch with harness | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Unweighting system (Airwalk) | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Handrail crossbar | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Bicycle & Wheelchair use | | | | | | | | | ○ | ○ | ○ |
| Belt for ski applications | | | | | | | | | ○ | ○ | ○ |
| Handrail long 2 pillars | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ● | ● | ● |
| Adjustable handrail | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| Arm support | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Protocols | | | | | | | | | | | |
| Acceleration levels | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 |
| Exercise profile | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 |
| Definable profile | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| Test profile | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Hardware | | | | | | | | | | | |
| Heart Rate Control Load | ● (DE LC only) | ● (DE LC only) | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| User Terminal | ● (DE LC only) | ● (DE LC only) | ● | ● | ● | ● (D & DE only) | ● | ● | ● | ● | ● |
| RS232 com1 | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| RS232 com2 | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ● | ● | ● |
| RS232 com 3 and com4 | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Motor System | 1-phase | 1-phase | 1-phase | 1-phase | 1-phase | 1-phase | 1-phase | 3-phase | 3-phase | 3-phase | 3-phase |
| Motor Capacity (kW) | 2.2 | 2.2 | 2.2 | 2.2 | 3.3 | 3.3 | 3.3 | 4.3 | 11 | 11 | 11 |
| Motor Voltage (V) | 200-240 | 200-240 | 200-240 | 200-240 | 230 | 230 | 230 | 400 | 400 | 400 | 400 |
| CE0123, MDD conformity | | ● | | ● | | ● | ● | ● | ● | ● | ● |
| Software | | | | | | | | | | | |
| Para control | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Para graphics | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ● | ● | ● |
| Para analysis | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |